

**AiO<sup>3</sup>**—builds upon our original AiO with new features, while maintaining its core functions as a multipurpose audio interfacing tool. It has been redesigned to address up-to-date audio needs in the professional AV market.

As well as retaining the original AiO's features, this new and improved version has VU metering of input or output signals via a mix control to allow Headphone monitoring (with personal volume control), plus switchable 48V Phantom power for your condenser microphones.

## Main Features

- Balanced audio Input and Output on industry standard XLR
- LED VU monitoring of Input and Output
- USB powered
- Line or Mic level inputs
- Optional Phantom Power for Input when using powered condenser mics
- Ground lift switch on the output XLRs
- Independent variable input level control for Ch1 and Ch2

## 3 Year Limited Factory Warranty

### Specifications:

#### Power

USB powered 250mA Max 5V  
Switchable 48V Phantom Power

#### Signals

Balanced line level and/or headset (Desk PFL out)  
Audio line 0dB out  
Audio in 0dB and Mic -40dB  
Bandwidth 20Hz - 20kHz

#### Control Switches

Stereo/Mono, GND Lift, Phantom Power,  
In/Out monitor headphones Mix

#### Connections

USB A-B from host computer, Balanced XLR in and out

Note XLR cables are not included as standard.

Interspace Industries

Unit 1F Tewin Court, Tewin Road, Welwyn Garden City, AL7, UK

call: +44 (0) 1462 600 101 email: [moreinfo@interspaceind.com](mailto:moreinfo@interspaceind.com) web: [www.interspaceind.com](http://www.interspaceind.com)

Disclaimer: Whilst all care is taken to ensure accuracy, Interspace Industries Ltd accepts no responsibility for any errors or omissions, whether implied or otherwise interpreted. All specifications subject to change without notice.



## The Next Stage in Professional Audio Interfacing



## Accessories

USB A-B cable supplied

**Note:** Do not use at high levels—Take care of your hearing!

